

1/6  
FIG. 1





FIG. 2



2/6

FIG. 3A

**300**  
Name = IBM  
DomainName = ibm.com

FIG. 3B

**350**  
Organization(DomainName="ibm.com")

FIG. 4A

**400**  
HostName = ExampleHost  
Architecture = pSeries

FIG. 4B

**450**  
Organization(DomainName="ibm.com"),ComputerSystem(HostName="ExampleHost")

3/6

FIG. 5A

**500**  
Name = EMACS  
ProcessID = 16325

FIG. 5B

**550**  
Organization(DomainName="ibm.com"), ComputerSystem(HostName="ExampleHost"),  
Application(ProcessID="16325")

FIG. 6A


**600**  
Name = Apache HTTP Server  
**610** — URL = http://example.ibm.com:8080

FIG. 6B

**650**  
Server(URL=http://example.ibm.com:8080)

4/6

FIG. 7



5/6  
FIG. 8




FIG. 9

**900**

```
<?xml version="1.0" ?>

<xsd:schema xmlns:xsd="http://www.w3.org/2001/XMLSchema">

<!-- *****
<!-- The root element defines a naming rule.
<!-- *****
<xsd:element name="NamingRule" minOccurs="0"> --910
  <xsd:complexType>
    <xsd:sequence>
      <xsd:element name="Key" maxOccurs="unbounded"> --920
        <xsd:complexType>
          <xsd:attribute name="Name" type="xsd:QName" use="required"/> --930
        </xsd:complexType>
      </xsd:element>
    </xsd:sequence>
    <xsd:attribute name="ScopingEntity" type="xsd:QName" use="optional"/> --940
  </xsd:complexType>
</xsd:element>
</xsd:schema>
```